

# Allsteel Aspect™ Demountable Partition



This Environmental Product Declaration, covering all life cycle stages, was prepared in conformity with ISO 14025, ISO 14044, and ISO 21930, and in accordance with the Earthsure Product Category Rule 30162403:2014 for Interior Wall Systems. PCR Review Chair Thomas Gloria, LCACP# 2008-3. EPDs prepared under other programs may not be comparable.



SCS-EPD-05292 | Dates of Validity: January 14, 2019 to January 13, 2024

# Allsteel®

**Product:** The Aspect demountable partition system is an elegant solution that creates offices and conference rooms within an open floorplan, while maintaining openness and transparency desired in today's modern workplace. A continuous reveal and low-profile trim seamlessly frame the exterior of each element, and a variety of glass, door, hardware, and finish options provide choice in crafting a unique brand story. This EPD is for an Aspect demountable partition system.

**Producer:** At Allsteel, we demystify the office planning process by helping our customers align their workplace strategy with their business strategy. With an accessible team and an adaptable portfolio of systems, seating, casegoods, tables, collaborative furniture and architectural walls, we address our customers' needs for today and tomorrow.

### Independent Verification

Independent verification of the declaration and data, according to ISO 14025:

internal     external








**Thomas Gloria**, t.gloria@industrial.ecology.com, LCACP#: 2008-3

Summary of Life Cycle Impacts and Inventory		
per m <sup>2</sup> -30 yr-meeting IBC requirements for interior walls		
Climate Change	92	kg CO <sub>2</sub> -eq
Acidification	0.57	kg SO <sub>2</sub> -eq
Eutrophication	0.28	kg N-eq
Ozone Depletion	1.1x10 <sup>-5</sup>	kg CFC-11-eq
Photochemical Smog	7.3	kg O <sub>3</sub> -eq
Ecotoxicity	480	CTUe
Human Health – Air	0.11	kg PM2.5-eq
Primary Energy Consumption	880	MJ non-renewable
	260	MJ renewable
Freshwater Consumption	3,400	L
Waste Production	2.5x10 <sup>-2</sup>	kg hazardous
	21	kg non-hazardous
Material Resource Consumption	INA	kg non-renewable
	0.0	kg renewable
Land Use	52	m <sup>2</sup> -yr

INA: Indicator not assessed

## LIFE CYCLE IMPACT ASSESSMENT RESULTS

For one square meter of interior wall conforming to the International Building Code for thirty years, using TRACI 2.1 Life Cycle Indicators (CML in parentheses):

Life Cycle Impact	Total	Stage I Production	Stage II Installation	Stage III Use	Stage IV End of Life	Units
 Climate Change	92	71	21	0.0	0.38	kg CO <sub>2</sub> eq
	(92)	(71)	(21)	(0.0)	(0.38)	kg CO <sub>2</sub> eq
 Acidification	0.57	0.48	9.2x10 <sup>-2</sup>	0.0	1.9x10 <sup>-3</sup>	kg SO <sub>2</sub> eq
	(0.56)	(0.48)	(8.4x10 <sup>-2</sup> )	(0.0)	(1.6x10 <sup>-3</sup> )	kg SO <sub>2</sub> eq
 Eutrophication	0.28	0.19	8.6x10 <sup>-2</sup>	0.0	1.6x10 <sup>-3</sup>	kg N eq
	(0.15)	(0.11)	(4.7x10 <sup>-2</sup> )	(0.0)	(8.0x10 <sup>-4</sup> )	kg PO <sub>4</sub> <sup>3-</sup> eq
 Ozone Depletion	1.1x10 <sup>-5</sup>	7.6x10 <sup>-6</sup>	3.4x10 <sup>-6</sup>	0.0	7.6x10 <sup>-8</sup>	kg CFC-11 eq
	(8.4x10 <sup>-6</sup> )	(5.8x10 <sup>-6</sup> )	(2.6x10 <sup>-6</sup> )	(0.0)	(5.8x10 <sup>-8</sup> )	kg CFC-11 eq
 Photochemical Smog	7.3	5.6	1.7	0.0	3.9x10 <sup>-2</sup>	kg O <sub>3</sub> eq
	(2.4x10 <sup>-2</sup> )	(2.0x10 <sup>-2</sup> )	(4.4x10 <sup>-3</sup> )	(0.0)	(9.1x10 <sup>-5</sup> )	kg C <sub>2</sub> H <sub>4</sub> eq
 Ecotoxicity	480	250	134	0.0	92	CTUe
	(53)	(37)	(12)	(0.0)	(3.5)	kg 1,4-DB eq
 Human Health-Air	0.11	8.2x10 <sup>-2</sup>	3.0x10 <sup>-2</sup>	0.0	2.8x10 <sup>-4</sup>	kg PM <sub>2.5</sub> eq

## LIFE CYCLE INVENTORY INFORMATION

For one square meter of interior wall conforming to the International Building Code for thirty years:

Inventory Item	Amount	Units
Primary Energy Consumption	880	MJ non- renewable
	260	MJ renewable
Freshwater Consumption	3,400	L
Waste Production	$2.5 \times 10^{-2}$	kg hazardous
	21	kg non-hazardous
Material Resource Consumption	INA	kg non-renewable
	0.0	kg renewable
Land use	52	m <sup>2</sup> yr

INA: Indicator not assessed

## HAZARDOUS MATERIAL CONTENT

For one square meter of interior wall conforming to the International Building Code for thirty years (at least 0.1% using California DTSC Candidate Chemical List).

Material	CAS number	Amount (%)
Aluminum	7429-90-5	9.2%
Zinc	7440-66-6	0.05%

## ADDITIONAL ENVIRONMENTAL INFORMATION

VOC emissions per BIFMA X7.1	Passed
Recycled Content	3.7% (pre-consumer)
	1.2% (post-consumer)
Other environmental certification programs	Indoor Advantage™ Gold; level@2

## ADDITIONAL LIFE CYCLE IMPACTS

Additional life cycle impact results are reported below as optional parameters of concern. These impacts are calculated using the LEO-SCS-002 framework, which complements the ISO 14044 standard for LCA with additional guidance on conducting a more comprehensive impact assessment. Results are shown for one square meter of interior wall conforming to the International Building Code for thirty years.

Category Indicator (LEO-SCS-002 Parameters)	Total	Units
Global Climate Change	87	kg CO <sub>2</sub> eq
Ocean Acidification	120	kg H <sub>2</sub> CO <sub>3</sub> eq
Energy Resource Depletion	430	MJ eq

Some equivalency factors were determined with the purpose of communicating and interpreting critical environmental impact results in simplified terms for better understanding. The table below provides a summary of select LCI inventory results and impact indicators translated to routine activities which will aid a consumer interpret the scale of potential environmental impact attributed to the product. For example, the primary energy demand for the 1 m<sup>2</sup> of the Allsteel Beyond movable wall system is equivalent to operating a refrigerator for approximately 58 days.

Category Indicator	Life Cycle Impact Assessment Results for 1 m <sup>2</sup> of wall system for 30 years	Basis of Equivalency Metric	1 m <sup>2</sup> of wall system maintained for 30 years
Global Warming Potential (IPCC 100 year time horizon)	72 kg CO <sub>2</sub> eq	Number of miles driven in a typical passenger vehicle	170 miles
Net Water Use	3,440 Liters	Number of cycles run in a dishwasher	77 cycles
Primary Energy Demand	1,100 MJ	Number of days operating a refrigerator	58 days
Global Climate Change (LEO-SCS-002)	87 kg CO <sub>2</sub> eq	Number of miles driven in a typical passenger vehicle	190 miles
Energy Resource Depletion (LEO-SCS-002)	430 MJ eq	Number of days operating a refrigerator	23 days

# Allsteel®

For more information contact:

**Allsteel Inc**

2210 Second Avenue, Muscatine, IA 52761  
800.255.7833 | <http://www.allsteeloffice.com/>



**SCS Global Services**

2000 Powell Street, Ste. 600, Emeryville, CA 94608 USA  
Main +1.50.452.8000 | fax +1.510.452.8001